

DUOPLAIN

TECHNICAL DATA

Size (overall)	268 × 330mm
Minimum Pitch (The minimum pitch is based on a maximum rafter length of 10 metres. For rafter lengths greater than this, please contact the Technical Solutions on 03708 702595)	25°
Maximum Pitch (subject to fixing specification)	90°
Minimum Headlap	80mm
Maximum Headlap	95mm
Minimum Gauge/Batten Spacing	173mm
Maximum Gauge/Batten Spacing	188mm
Hanging Length (approx.)	245mm
Cover (all figures are net and do not allow for wastage) Linear cover of 1 tile Covering capacity	300mm 17.7 tiles/m ² (at 188mm gauge)
Weight per pallet, including pallet (approx.) per 1000	55kg/m ² (at 173mm gauge) 0.91 tonnes 3.10 tonnes
Battens Required (at max. gauge)	5.26m/m ²
Batten Size Rafter centres up to 450mm Rafter centres up to 600mm	38 × 25mm 50 × 25mm
Nail Size for Tiles* (Depending on fixing specification)	45 × 3mm (A/A) or 45 × 3.35mm (S/S)
Pallet Quantities	Tiles per pallet 288 / Tiles per pack 6 / Packs per pallet 48

* (A/A) Aluminium Alloy (S/S) Stainless Steel Ring Shank