



# ROSEMARY CLAY CRAFTSMAN

## TECHNICAL DATA

<b>Size</b> (overall)	265 x 165mm
<b>Minimum Pitch</b>	35°
<b>Maximum Pitch</b> (subject to fixing specification)	90°
<b>Minimum Headlap</b>	Below 90° 65mm / at 90° 35mm
<b>Maximum Headlap</b>	88mm
<b>Minimum Gauge/Batten Spacing</b>	88mm
<b>Maximum Gauge/Batten Spacing</b>	below 90° 100mm / at 90° 115mm
<b>Hanging Length</b> (approx.)	255mm
<b>Cover</b> (all figures are net and do not allow for wastage)	
Linear cover of 1 tile	165mm
Covering capacity	below 90° 60 tiles/m <sup>2</sup> / at 90° 52 tiles/m <sup>2</sup>
<b>Weight</b>	below 90° 78kg/m <sup>2</sup> / at 90° 68kg/m <sup>2</sup>
per pallet, including pallet (approx.)	0.95 tonnes
per 1000	1.30 tonnes
<b>Battens Required</b> (at max. gauge)	below 90° 10.0m/m <sup>2</sup>
<b>Batten Size</b>	
Rafter centres up to 600mm	38 x 25mm
<b>Nail Size for Tiles*</b>	40 x 2.65mm (A/A)
<b>Pallet Quantities</b>	Tiles per pallet 720 / Tiles per pack 12 / Packs per pallet 60

\* (A/A) Aluminium Alloy